

# *Default ntp.conf for FreeBSD 8.0*

Tony Finch <fanf@freebsd.org>  
channelling David Malone <dwmalone@freebsd.org>

20 September 2009

```
#  
# $FreeBSD: src/etc/ntp.conf,v 1.2 2009/07/13 05:51:33 dwmalone Exp $  
#  
# Default NTP servers for the FreeBSD operating system.  
#  
# Don't forget to enable ntpd in /etc/rc.conf with:  
# ntpd_enable="YES"  
#  
# The driftfile is by default /var/db/ntpdrift, check  
# /etc/defaults/rc.conf on how to change the location.  
#
```

```
#  
# The following three servers will give you a random set of three  
# NTP servers geographically close to you.  
# See http://www.pool.ntp.org/ for details. Note, the pool encourages  
# users with a static IP and good upstream NTP servers to add a server  
# to the pool. See http://www.pool.ntp.org/join.html if you are interes  
#  
# The option 'iburst' is used for faster initial synchronisation.  
# The option 'maxpoll 9' is used to prevent PLL/FLL flipping on FreeBSD  
#  
server 0.freebsd.pool.ntp.org iburst maxpoll 9  
server 1.freebsd.pool.ntp.org iburst maxpoll 9  
server 2.freebsd.pool.ntp.org iburst maxpoll 9  
#server 3.freebsd.pool.ntp.org iburst maxpoll 9
```

```
#  
# If you want to pick yourself which country's public NTP server  
# you want sync against, comment out the above servers, uncomment  
# the next ones and replace CC with the country's abbreviation.  
# Make sure that the hostnames resolve to a proper IP address!  
#  
# server 0.CC.pool.ntp.org iburst maxpoll 9  
# server 1.CC.pool.ntp.org iburst maxpoll 9  
# server 2.CC.pool.ntp.org iburst maxpoll 9
```

```
#
# Security: Only accept NTP traffic from the following hosts.
# The following configuration example only accepts traffic from the
# above defined servers.
#
# Please note that this example doesn't work for the servers in
# the pool.ntp.org domain since they return multiple A records.
# (This is the reason that by default they are commented out)
#
#restrict default ignore
#restrict 0.pool.ntp.org nomodify nopeer noquery notrap
#restrict 1.pool.ntp.org nomodify nopeer noquery notrap
#restrict 2.pool.ntp.org nomodify nopeer noquery notrap
#restrict 127.0.0.1
#restrict -6 ::1
#restrict 127.127.1.0
```

```
#
# If a server loses sync with all upstream servers, NTP clients
# no longer follow that server. The local clock can be configured
# to provide a time source when this happens, but it should usually
# be configured on just one server on a network. For more details see
# http://support.ntp.org/bin/view/Support/UndisciplinedLocalClock
# The use of Orphan Mode may be preferable.
#
#server 127.127.1.0
#fudge 127.127.1.0 stratum 10
```

*Watch out for Mergemaster!*